


LIFEGARD[®] Vue Central Station



LIFEGARD VUE is a powerful Central Nurses Station that provides central and remote monitoring of multiple devices, and patient parameters.

Intuitive and easy to use

- Simplified ADT makes adding devices and patients a snap.
- Customize the snapshot view for monitoring specific patient values.
- Waveform and Detail view offers enhanced clinical assessment.

Features and Technologies

- Real-time waveforms
- Graphical Trends
- Tabular Trends
- Reports include snapshots, log of events, log of pagers sent, and more



Remote Monitoring

LIFEGARD® Vue Central Station

LIFEGARD VUE is a powerful Central Nurses Station that provides central and remote monitoring of multiple devices, and patient parameters.

Powered by
BERNOULLI®



Workstation

CPU: Intel Pentium III
Video: 1024 x 768 with 16 bit color depth
RAM: 512 MB
Inputs: Space saving keyboard, scrolling mouse
Hard Disk: 40 GB
CD-ROM: 8X Slimline DVD-ROM
Network: Ethernet 10/100 NIC
Serial Ports: (2) DB9 RS-232
Operating System: Microsoft Windows XP Pro
USB Ports: 8 Ports

Touchscreen Display

Viewable Size: 17" diagonal
Resolution: 1024 dots x 768 lines (XGA)
Display type: Active Matrix LCD (TFT)
Touchscreen Technology: Resistive or Surface Acoustic Wave
Touchscreen Resolution: 9 points per inch
Touchscreen Interface: USB or RS-232

Paging System

Interface Protocols: TAP, COMP1, COMP2, or WaveWare proprietary via DIP switch
Frequency: VHF - 148-174 MHz, UHF1 - 400-430 MHz, UHF2 - 440-470 MHz
Power Supply: 12VDC 2A AC/DC Adapter
Dimensions:
Size/Weight: 8.5"H x 8.5"W x 2"D, 1.5 lb.
RF Power Out: 5 Watts Nominal, configurable to 2 Watts

Device Bridge

Frequency Range: 2.4 to 2.5 GHz
Modulation: Direct Sequence Spread Spectrum (DSSS)
Radio Data Rate: 11 Mbps
Radio Standards: IEEE802.11b wireless LAN
TX Max Radiated: EIRP FCC Part 15.247, 15.205, 15.209
Security: WEP, WPA, LEAP, PEAP, EAP, AES

Access Point

Frequency Range: 2.4 to 2.5 GHz
Modulation: Direct Sequence Spread Spectrum (DSSS)
Radio Data Rate: 11 Mbps
Radio Standards: IEEE 802.11b or 802.11g wireless LAN
TX Max Radiated: EIRP FCC Part 15.247, 15.205, 15.209
Security: Wired Equivalent Privacy (WEP/WPA)
Network Connection: Ethernet, 10BaseT UTP (RJ-45)
Antenna: Spherical pattern, 11.25" tall

Wired Specifications

Device Server: RS232/422 Compatible
Serial Connection: Female DB25 connector (DCE pin out)
Network Connection: Ethernet, 10BaseT UTP (RJ-45)
Baud Rate: 9600-115,200

Router (minimum specifications)

LAN Port: (8) 10/100 RJ-45 Ports
WAN Port: (1) 10BaseT Broadband Port
Uplink Port: (1) 10BaseT/100BaseTX RJ-45

LIFEGARD II Monitor Models Supported

AN4320P Basic Monitor (EGC, Resp, Temp, NIBP and SpO2) with integrated printer
AN4320P Basic Monitor (EGC, Resp, Temp, NIBP and SpO2) with integrated printer
AN4320P Basic Monitor (EGC, Resp, Temp, NIBP and SpO2) with integrated printer
AN4320P Basic Monitor (EGC, Resp, Temp, NIBP and SpO2) with integrated printer

CAS Medical Systems, Inc.
44 East Industrial Road
Branford, CT 06405 USA
Telephone: 203 488 6056
Toll Free: 800 227 4414
www.casmed.com



ISO 13485
Certificate Number FM 72259

Dealer Imprint